

New York State Marine Patrol Quick Reference Guide - Pleasure Vessels



	LAW SECTION	Less than 16' to less than 16' 26'		26' to less than	46' to less than 65'	65' and Greater	Rowboats, Canoes, Kayaks	PWC	PWC LAW
		Class A	Class 1	Class 2	Class 3	Class 4	Non-Motorized		SECTION
Unregistered Vessel	2251.1 VTL	REQUIRED						REQUIRED	2251.1 VTL
Failure to Carry Registration Certificate	2253.2 VTL	REQUIRED						REQUIRED	2253.2 VTL
Failure/Improper Display Registration Numbers	2253.3 VTL	REQUIRED - Documented Vessels Exempt						REQUIRED	2253.3 VTL
Validation Stickers Not Displayed	2251.1 VTL	REQUIRED						REQUIRED	2251.1 VTL
Validation Stickers Improper Display	2253.4 VTL	REQUIRED						REQUIRED	2253.4 VTL
PFD's (Life Jackets)	40.1(a)	REQUIRED - One Wearable USCG Approved PFD for Each Person on Board						REQUIRED TO BE WORN	73-a.1(a)
Under 12 not wearing PFD	40.1(d)	REQUIRED IF NOT WITHIN FULLY ENCLOSED CABIN					REQUIRED		
Failure to Wear PFD Nov 1 - May 1	40.1(e)	REQUIRED LESS THAN 21'					REQUIRED LESS THAN 21'		
Throwable Device	40.1(b)	REQUIRED - USCG APPROVED NOT REC					NOT REQUIRED		
Sound Signaling Device	9 NYCRR 445.1 (Rule 33)	REQUIRED- All Vessels - Mouth Whistle Acceptable For Vessels Less Than 12 meters (39 feet)						REQUIRED	73-a.1(c)
Anchor & Line	40.3	REQUIRED							
Backfire Flame Arrestor	40.4	REQUIRED - Gasoline Powered Engines Except Outboard Motors						REQUIRED	73-a.1(b)
Fire Extinguisher (USCG Approved)	40.6(a)	Boats of Op		TWO B-1 wo B-2, Fixed Fire Ex a Cover One B-1 Extin		MUST MEET FEDERAL REQUIREMENTS			
Ventilation - Natural	40.8	REQUIRED - Vessels of Closed Construction						REQUIRED	73-a.1(c)
Daytime Visual Distress Signal	40.7	REQUIRED - USCG Requirements						REQUIRED - USCG Requirements or 1'x1' Distress Flag	73-a.1(c)
Nighttime Visual Distress Signal	40.7	REQUIRED - USCG Requirements							
Bell	9 NYCRR 445.1 (Rule 33)	REQUIRED							
Navigation Lights	9 NYCRR 445.1 (Rule 22- 31)	REQUIRED - Night and Restricted Visibility							
Muffled Exhaust	44.4	REQUIRED - Execpt for Racing Boats, Manufacturer Test Boats, Pre-1965 Vessels						REQUIRED	44.4
Engine Cut-Off Lanyard								REQUIRED	73-a.1d
Excessive Noise Levels	44.2(a) 44.2(b)	Stationary Test - SAE J-2005 - 90dB(A) Drive by Test - SAE J-1970 - 75dB(A)						Stationary Test Drive by Test	44.2(a) 44.2(b)